

Model Area 51 Tube Transducer



Area 51 TT Multi-Pattern Remotely-Variable Tube Microphone, Power Supply, Ring/Shock Combination Mount, Best Flight Case, Multi-Pin Cable, Windscreen, Factory Stock 6072 Military Grade Vacuum Tube.

Area 51 TT SPECIFICATIONS

TYPE: True Condenser Pressure Gradient Mic with Dual 1" Six Micron Diaphragms and Valve Pre-Amplifier

POLAR PATTERN: 9 Polar Patterns Including Omni, Cardioid, Figure 8 and Six Intermediate Positions

SENSITIVITY: 1mV/Pa = -37dBV (0 dBV = 1v/Pa)

FREQUENCY RANGE: 20 Hz to 20k Hz

IMPEDANCE: < 250 Ohms

RECOMMENDED LOAD IMPEDANCE: > 1000 Ohms

MAX SPL FOR 1% THD @ 1000 Hz: 125 dB

EQUIVALENT NOISE LEVEL: IEC 286-4 (A Weighted) 20 dB Typical

S/N RATIO @ 1Pa: 76 dB

POWER REQUIREMENT: Dedicated ADK Power Supply

REL. HUMIDITY: 90% (C) / 85% (C)

CONNECTOR: 7 Pin Multi-Pin Cable (Supplied)

SIZE: Diameter 53mm (2.1") Length 225mm (8.9")

NET WEIGHT: 750gm (26.5oz)

APPLICATIONS

Male and Female Vocals, Acoustic and Electric Guitar, Reed Instruments (Sax), Strings (Violin, Viola, Cello, and Contrabass), Drum Overheads, or anywhere you would use a Vintage Tube Microphone. Great for Broadcast Applications, too! Multi-Patterns offer you a Palette of tone-colors / tone-textures. Amazing!

CONFIGURATIONS

Area 51 TT - Multi-pattern Tube Mic / Power Supply / Ring-Shock Mount / Multi-pin Cable / Windscreen All Packaged in a Premium Flight Case. Lenny Kravitz to Kathy Mattea – the TT has an all-star fan club!

* Specifications subject to change without notice. © 2003 ADK Microphones. All Rights Reserved.