

# BXL450

# ULTRABASS

## Technical Specifications

GB

Version 1.1 December 2005



[www.behringer.com](http://www.behringer.com)



# ULTRABASS

**45-Watt 2-Channel Bass Workstation with Original BUGERA™ 10" Speaker and FBQ Spectrum Analyzer**



- ▲ Powerful 45-Watt Bass Workstation in wedge-shaped cabinet
- ▲ Original BUGERA™ 10" special high-impact cone speaker
- ▲ Clean channel with dedicated Gain control
- ▲ Distortion channel with dedicated Gain, Shape and Level controls
- ▲ Ultra-musical, active 5-band graphic EQ with FBQ Spectrum Analyzer
- ▲ Revolutionary “See what you play” FBQ frequency indicator for instant sound shaping
- ▲ Musical opto-limiter for ultimate volume without distortion
- ▲ Separate headphone output—perfect for quiet practicing
- ▲ CD input allows you to play along to your favorite music
- ▲ High-quality components and exceptionally rugged construction ensure long life
- ▲ Conceived and designed by BEHRINGER Germany

BXL450

## SPECIFICATIONS

BXL450	
<b>AUDIO INPUTS</b>	
Instrument input	¼" TS
Input impedance	250 kOhm
CD input	RCA
Input impedance	40 kOhm
<b>AUDIO OUTPUTS</b>	
Phones Out	¼" TRS stereo
<b>SYSTEM SPECIFICATIONS</b>	
Power amp output	45 W @ 4 Ohm
<b>LOUDSPEAKERS</b>	
Type	10"
Impedance	BUGERA™ Classic Tone Series
Model	4 Ohm
Power handling	50 W
<b>POWER SUPPLY</b>	
Mains voltage	USA/Canada 120 V~, 60 Hz
	Europe/U.K./Australia 230 V~, 50 Hz
	Japan 100 V~, 50 - 60 Hz
	China/Korea 220 V~, 50 Hz
	General export model 120/230 V~, 50 - 60 Hz
Power consumption	max. 75 Watt
Fuses 100 - 120 V~	T 2.5 A H 250 V
Fuses 200 - 240 V~	T 1.25 A H 250 V
Mains connection	Standard IEC receptacle
<b>DIMENSIONS/WEIGHT</b>	
Dimensions (H x W x D)	459 x 361 x 349 mm
	18" x 14.2" x 13.7"
Weight	13.90 kg
	30.6 lbs



BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may differ from those listed or illustrated.

Technical specifications and appearance subject to change without notice. The information contained herein is correct at the time of printing. The names of companies, institutions or publications pictured or mentioned and their respective logos are registered trademarks of their respective owners. Their use neither constitutes a claim of the trademarks by BEHRINGER® nor affiliation of the trademark owners with BEHRINGER®. BEHRINGER® accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph or statement contained herein. Colours and specification may vary slightly from product. Products are sold through our authorised dealers only. Distributors and dealers are not agents of BEHRINGER® and have absolutely no authority to bind BEHRINGER® by any express or implied undertaking or representation. No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of BEHRINGER Spezielle Studiotechnik GmbH. BEHRINGER® is a registered trademark.

ALL RIGHTS RESERVED. © 2005 BEHRINGER Spezielle Studiotechnik GmbH,  
Hanns-Martin-Schleyer-Str. 36-38, 47877 Willich-Münchheide II, Germany.  
Tel. +49 2154 9206 0, Fax +49 2154 9206 4903