

Durable road case Durable road case CALL: 503-682-6933 FAX: 503-682-7114 3 x F-10 3 x F-10 1 x F-12 1 x F-12

2 x F-15

www.audixusa.com









Now everyone can afford Audix quality and capture the sound of any drum or percussion instrument. Here are prepackaged microphones which are tough, durable, and offer the type of sonic performance associated with microphones costing much more.

The two packages are available complete with foam padded road case, and all Fusion mics come with integral mic clips (F10 and F12) or mic stand adapters (F15).

All mics will be available individually and carry a 1 year warranty.

Optional Fusion Accessories

- 1) D-vice: drum clip with a nylon rim mount
- 2) D-flex: flexible dual pivot rim mount clip
- 3) Space-saver mic cable (25') with right angle connector
- 4) Tripod: compact drum stand for F-12









	F-10	F-12	F-15
Application	Snare, Toms Bongos, Quinto, Hi-hat, Shekere, Congas, Timbales	Kick Drum, Floor Tom, Djembe	Cymbals, Overheads, Hi-hat, Goodie Table
Features	Tailored frequency response provides upper mid-range attack and clarity	Extended low end response for fat, punchy sound	Captures wide sound field of the cymbals and transients. Adds dimension and realism
Transducer Type	Dynamic	Dynamic	Condenser 9 - 52 volts phantom
Frequency Response	50 Hz - 12 kHz	40 Hz - 10 kHz	100 Hz - 20 kHz
Polar Pattern	Cardioid	Cardioid	Cardioid
Output Impedance	250 Ohms	250 Ohms	200 Ohms
Open Circuit Sensitivity (1 k @ 94 dB SPL)	1.8 mV/Pa	2.1 mV/Pa	9.3 mV/Pa
Capsule technology	Double dome	Double dome	Back plate electret
Maximum SPL	135 dB	135 dB	135 dB
Off-axis rejection	>20 dB	>20 dB	>15 dB
Housing	Die cast zinc, black e-coat	Die cast zinc, black e-coat	Die cast zinc, black e-coat
Weight	7.1 oz	7.4 oz	6.5 oz



FUSION 4

Fusion 4 package contains: 1 x Durable road case 3 x F-10 snare / tom mic 1 x F-12 kick / floor tom mic



FUSION 6

Fusion 6 package contains:

- 1 x Durable road case
- 3 x F-10 snare / tom mic
- 1 x F-12 kick / floor tom mic
- 2 x F-15 overhead mic plus 2 clips













