

B2031

TRUTH

Technical Specifications

Version 1.0 May 2000

ENGLISH



www.behringer.com

TRUTH

2-way active high-resolution studio monitor

- ▲ Ultra-linear frequency response from 50 Hz to 21 kHz
- ▲ Two built-in high power amps with 150/75 Watts and enormous power reserves
- ▲ Extremely high-resolution tweeter with ferrofluid-cooled titanium dome
- ▲ Long-throw 8.75" woofer with special polycarbonate diaphragm and sturdy cast aluminum chassis
- ▲ Controlled dispersion pattern through phase-optimized wave guide system
- ▲ Extremely large "sweet spot" through vertically/horizontally balanced dispersion characteristics
- ▲ Active frequency crossover with 4th order Linkwitz-Riley filters
- ▲ Flexible adaptation to room acoustics, incl. subwoofer operation
- ▲ Overload protection through separately controlled limiter for low- and high-frequency ranges
- ▲ Automatic standby switching
- ▲ Electromagnetic shielding for minimum interference
- ▲ Delivery of "matched pairs". Measurement protocol included
- ▲ Low-vibration E1 MDF cabinet
- ▲ Servo-balanced inputs on XLR and TRS connectors
- ▲ Manufactured under ISO9000 certified management system

SPECIFICATIONS

Audio inputs

XLR	servo-balanced input
1/4" jack	servo-balanced input
Impedance	20 kOhms
Max. input level	+22 dBu

Loudspeaker

Tweeter	25 mm ferrofluid-cooled dome
Woofers	22 cm (8.75") polycarbonate diaphragm

Amplifiers

Low frequency	max. 150 watts
High frequency	max. 75 watts
Noise (SPL @ 10 cm)	<10 dBA @ 1 m (each)

Crossover

Type	active, 4th order Linkwitz-Riley filter
Crossover frequency	2 kHz

System specifications

Bandwidth	50 Hz to 21 kHz
Sound pressure level	max. 116 dB SPL @ 1 m (pair)

Power supply

Mains voltages	U.S.A./Canada	120 V ~, 60 Hz
	U.K./Australia	240 V ~, 50 Hz
	Europe	230 V ~, 50 Hz
	general export model	100 - 120 V ~, 200 - 240 V ~, 50 - 60 Hz
Fuse	100 - 120 V ~ :	T 5.0 A H
	200 - 240 V ~ :	T 2.5 A H
Power consumption	210 watts, standby 27 watts	
Mains connection	standard IEC receptacle	

Physical

Dimensions (H * W * D)	15.75" (400 mm) * 9.85" (250 mm) * 11.42" (290 mm)
Net weight	approx. 15 kg (each)

The information contained in this sheet is subject to change without notice. No part of this sheet may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of BEHRINGER Spezielle Studiotechnik GmbH.

BEHRINGER is a registered trademark. ALL RIGHTS RESERVED.

© 2000 BEHRINGER Spezielle Studiotechnik GmbH.

BEHRINGER Spezielle Studiotechnik GmbH, Hanns-Martin-Schleyer-Str. 36-38, 47877 Willich-Münchheide II, Germany

Tel. +49 (0) 21 54 / 92 06-0, Fax +49 (0) 21 54 / 92 06-30
