BF-3 Flanger



A Legendary Flanging Pedal is Reborn.

Building on the 20-year legacy of the famous BOSS BF-2, the new BF-3 Flanger pedal gives guitarists and bassists an updated version of the classic BOSS flanger with the thickest stereo flanging sounds ever. Two new modes (Ultra and Gate/Pan) create flanging with incredible depth—even Slicer-type effects and sounds that seem to "swirl" around the listener. An instant classic.

- BOSS' best flanging effects in a compact pedal
- New Ultra and Gate/Pan modes for ultra-fat flanging with very low noise
- Momentary mode turns flanging on instantly
- Tap tempo adjustable via pedal
- Independent Guitar and Bass inputs and stereo outputs



*Actual product appearance may be subject to change without notice.

BF-3 Specifications

• Nominal Input Level -20 dBu • Input Impedance 1 M Ω • Nominal Output Level -20 dBu • Output Impedance 1 k Ω • Recommended Load Impedance 10 k Ω or greater • Delay Time 0.3 mS-14.4 mS (GUITAR IN), 0.3 mS-6.3 mS (BASS IN) • LFO Speed 100 mS-18 S • Residual Noise -95 dBu (HHF-A Typ.) • Control's Pedal Switch, MANUAL Knob, RES (resonance) Knob, DEPTH Knob, RATE Knob, MODE Knob • Indicator CHECK Indicator (Serves also as tempo and battery check indicator) • Connectors GUITAR IN Jack, BASS IN Jack, OUTPUT A (MONO) Jack, OUTPUT B Jack, AC adaptor Jack (DC 9 V) • Power Supply DC 9 V; Dry battery (9 V type) S-006P/9 V

(6F22/9 V), Dry battery (9 V type) 6AM6/9 V (alkaline), AC Adaptor (PSA-series: optional) ◆ Current Draw 39 mA (DC 9 V) *Expected battery life under continuous use: Carbon: 3 hours, Alkaline: 10 hours, These figures will vary depending on the actual conditions of use. ◆ Dimensions 73 (W) x 129 (D) x 59 (H) mm, 2-7/8 (W) x 5-1/8 (D) x 2-3/8 (H) inches ◆ Weight 420 g /15 oz (including Battery) ◆ Accessories Owner's Manual Dry battery (9 V type) S-006P/9 V (6F22/9 V) *The battery that was supplied with the unit is for temporary use-intended primarily for testing its operation. ◆ Options AC Adaptor PSA-Series

* 0 dBu = 0.775 Vrms.

* The specifications are subject to change without notice.