KONTOUR™ SERIES









WHAT YOU NEED TO KNOW

INSTALLING THE MONITOR MOUNT

The mounting surface thickness must be between 0.75"-2.5" (19-63 mm).

MOUNTING PATTERNS

Compatible with 75 x 75 mm and 100 x 100 mm VESA® patterns.

QUICK-CONNECT INTERFACE

Easily attach and remove interface from mounting head without removing monitor – no tools necessary!



FEATURES

HEAVY DUTY DESIGN Sleek, solidly constructed forged aluminum arms.

2 ULTIMATE FLEXIBILITY

Dynamic height adjustment using gas-spring technology for ideal positioning.

FAST INSTALLATIONSimple 3-step installation and integrated quick-connect interface for easy mounting and maintenance.

4 CABLE MANAGEMENT

Tool-free cable management covers for a clean, professional look.

5 CENTRIS® EXTREME TILT PATENTED FEATURE
Tilts -75°/+10° for an ultimate ergonomic solution.

SPECIFICATIONS	
Depth from Back of Desk	2.09" (53 mm)
Max. Extension	19.9" (505 mm)
Tilt	-75° / +10°
Height Assist	13" (330 mm)
Weight Capacity	5–25 lbs (2.3–11.3 kg)
Colors	Black, Silver

RECOMMENDED ACCESSORY

KRA202 Grommet Accessory

TECHNICAL DRAWINGS





