

CHART OF STANDARD U.S. FREQUENCIES

Please consult this chart for frequency selection information for all wireless system ordering

SINGLE CHANNEL RECEIVER VHF

| FREQUENCY | CHANNEL | MODEL | | | | |
|-------------|---------|-------|-------------|------------|-----|-----|
| | | DKW-1 | ENCORE I/II | ENCORE 200 | 351 | 151 |
| 170.245 MHz | G1 | | | ✓ | | ✓ |
| 171.905 MHz | A | ✓ | ✓ | ✓ | ✓ | ✓ |
| 185.150 MHz | B | ✓ | ✓ | ✓ | ✓ | |
| 191.300 MHz | H | ✓ | ✓ | ✓ | | ✓ |
| 197.150 MHz | N | ✓ | ✓ | ✓ | ✓ | |
| 203.400 MHz | F | ✓ | ✓ | ✓ | ✓ | |
| 209.150 MHz | D | ✓ | ✓ | ✓ | ✓ | |
| 215.200 MHz | E | ✓ | ✓ | ✓ | ✓ | |

SINGLE CHANNEL MULTI RECEIVER VHF

| FREQUENCY | CHANNEL | MODEL | |
|---|--------------|-------------|-----------|
| | | ENCORE DUET | 401X QUAD |
| 202.100, 209.150 MHz | A1 & D | ✓ | |
| 171.905, 203.400 MHz | A & F | ✓ | |
| 215.200, 203.400 MHz | E & F | ✓ | |
| 206.350, 212.100 MHz | P & R | ✓ | |
| 215.200, 191.300 MHz | E & H | | |
| 170.245, 197.150 MHz | G & N | | |
| 185.150, 209.150 MHz | B & D | ✓ | |
| 171.905, 185.150, 209.150, 197.150 MHz | A, B, D, & N | | ✓ |
| 173.800, 203.400, 191.300, 215.200 MHz | E4, F, H, E | | ✓ |

SINGLE CHANNEL MULTI RECEIVER UHF

| FREQUENCY | CHANNEL | MODEL |
|------------|---------|-------|
| | | UHF-3 |
| 470.55 MHz | MU1 | ✓ |
| 480.55 MHz | MU2 | ✓ |
| 484.55 MHz | MU3 | ✓ |
| 493.55 MHz | MU4 | ✓ |
| 495.55 MHz | MU5 | ✓ |
| 509.55 MHz | MU6 | ✓ |

UHF-16 / U-1000 SERIES

Frequency ranges available between 726 - 863 MHz
Call for information on available ranges and their specific frequencies.

SINGLE CHANNEL RECEIVER UHF

| FREQUENCY | CHANNEL | MODEL | |
|-------------|---------|-------|--------|
| | | UHF-4 | UHF-10 |
| 800.200 MHz | 1 | ✓ | ✓ |
| 802.300 MHz | 2 | ✓ | ✓ |
| 803.300 MHz | 3 | ✓ | ✓ |
| 804.880 MHz | 4 | ✓ | ✓ |
| 794.900 MHz | U5 | ✓ | ✓ |
| 797.500 MHz | U6 | ✓ | ✓ |
| 796.300 MHz | U7 | ✓ | ✓ |
| 798.800 MHz | U8 | ✓ | ✓ |
| 804.900 MHz | U9 | ✓ | ✓ |

ALD-800/E03

| FREQUENCY | CHANNEL | MODEL | |
|-----------|---------|---------|-----|
| | | ALD-800 | E03 |
| 72.1 MHz | AA | ✓ | ✓ |
| 72.3 MHz | BB | ✓ | ✓ |
| 72.5 MHz | CC | ✓ | ✓ |
| 72.7 MHz | DD | ✓ | ✓ |
| 72.9 MHz | EE | ✓ | ✓ |
| 75.5 MHz | FF | ✓ | ✓ |
| 75.7 MHz | GG | ✓ | ✓ |
| 75.9 MHz | HH | ✓ | ✓ |

WA-120

| FREQ. | CH. | MODEL | FREQ. | CH. | MODEL | FREQ. | CH. | MODEL |
|-------------|-----|--------|-------------|-----|--------|-------------|-----|--------|
| | | WA-120 | | | WA-120 | | | WA-120 |
| 202.100 MHz | A1 | ✓ | 227.320 MHz | M1 | ✓ | 170.245 MHz | G1 | ✓ |
| 202.400 MHz | A3 | ✓ | 171.905 MHz | A | ✓ | 191.300 MHz | H | ✓ |
| 175.000 MHz | E3 | ✓ | 185.150 MHz | B | ✓ | 197.150 MHz | N | ✓ |
| 173.800 MHz | E4 | ✓ | 209.150 MHz | D | ✓ | 206.350 MHz | P | ✓ |
| 174.100 MHz | E5 | ✓ | 215.200 MHz | E | ✓ | 212.100 MHz | R | ✓ |
| 219.820 MHz | K1 | ✓ | 203.400 MHz | F | ✓ | | | |

WA-1620U

Frequency ranges available between 745 - 754.3 MHz
Call for information on available ranges and their specific frequencies.

PEM-500

16 channel selectable as listed: (channel) frequency

- (1) 694.300 MHz, (2) 694.900 MHz, (3) 695.600 MHz, (4) 696.300 MHz, (5) 696.900 MHz (6) 697.600 MHz,
(7) 698.300 MHz, (8) 698.900 MHz, (9) 699.600 MHz, (10) 700.300 MHz, (11) 700.900 MHz,
(12) 701.600 MHz, (13) 702.300 MHz, (14) 702.900 MHz, (15) 703.600 MHz, (16) 704.300 MHz

FREQUENCY ORDERING INFORMATION

Contact Nady Sales via the phone or fax number, or e-mail address provided for help with system design, application information, frequency coordination, custom frequency information on models not listed above and technical assistance, especially for multiple system operation. Please provide pertinent information when contacting Nady, including the city(s) where the system(s) will be operating and the frequencies of any other wireless equipment to be used at the same site.